



SPECIFICATIONS

MODEL NO.	Capacity *				Dimensions *** In.						Weight**** (lbs)		
	Pounds / hr	Boiler HP	Reserve Capacity (gal)	Tank Volume (gal)	A Tank Length	B Tank Dia.	C Overall Width	D Height	E** Water Inlet	F** Steam Inlet	Dry	Operating	Overfull
DAS2436	2415	70	46	92	54	24	34	104	3/4	3/4	1580	1965	2400
DAS3048	3,500	100	92	184	69	30	40	110	3/4	3/4	1,675	2,450	3,300
DAS3072	6,300	185	128	256	93	30	40	110	1	1	1,800	2,870	3,980
DAS3660	8,100	235	162	327	87	36	46	116	1	1	2,100	3,450	4,850
DAS3696	12,000	350	241	483	123	36	48	116	1 1/4	1 1/2	2,500	4,510	6,560
DAS36132	16,000	466	322	639	160	36	48	116	1 1/2	1 1/2	2,920	5,600	8,240
DAS4284	16,000	466	322	607	114	42	56	122	1 1/2	1 1/2	3,100	5,790	8,200
DAS4296	17,250	500	350	675	126	42	56	122	1 1/2	1 1/2	3,250	6,200	8,900
DAS42108	29,000	841	594	750	132	42	56	132	1 1/2	3	3,400	8,350	9,700
DAS42120	20,500	594	410	820	154	42	56	122	2	2	3,450	6,890	10,350
DAS4884	17,250	500	465	800	118	48	62	126	2	2	3,500	7,380	10,330
DAS48108	25,020	725	501	990	142	48	62	126	2	2	3,725	7,900	12,040
DAS48132	30,000	870	600	1,180	166	48	62	126	2	2	4,250	9,300	13,900
DAS5496	30,000	870	600	1,150	133	54	68	132	2	2	4,925	10,000	14,580
DAS54120	35,000	1,015	700	1,380	154	54	68	132	2 1/2	2 1/2	5,850	11,690	17,420
DAS60132	51,750	1,500	1,035	1,870	170	60	74	138	**	**	6,700	15,400	22,300

* - Capacity based on at least 10 minutes storage capacity.
 ** - Depends on pressure.
 *** - Standard frame height. Height dimensions may vary upon pump specification and job condition.
 **** - Weights vary based on pump selection job conditions.

RECOMMENDED CLEARANCES	PANEL	TOP	SIDE	BACK	MANHOLE SIDE
		36-48"	18"	24"	6-24"

Notes: Dimensions are for reference only. Due to continuous improvements, specifications are subject to change without notice.